

Appln No. 09/370,601

Amdt date December 29, 2003

Reply to Office action of September 29, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Cancelled).

2. (Currently Amended) An irrigation ablation probe comprising:

[a] an elongated probe body having a length between proximal and distal ends and comprising an elongated ablation electrode extending the length of the elongated probe body [at its distal end], wherein the elongated ablation electrode defines an inner cavity, the elongated ablation electrode having at least one irrigation opening through which fluid can pass from the inner cavity to the outside of the elongated ablation electrode, the elongated probe body being generally rigid from its proximal end to its distal end so that the body cannot bend during ablation, and wherein the elongated ablation electrode has an exposed distal portion that is generally straight and forms an angle  $\alpha$  greater than  $0^\circ$  with the remainder of the elongated probe body;

a sheath positioned on the elongated ablation electrode and configured to define the exposed distal portion;

means for introducing fluid into the inner cavity; and

a handle mounted at the proximal end of the elongated probe body, the handle comprising a housing having a generally open

Appln No. 09/370,601

Amdt date December 29, 2003

Reply to Office action of September 29, 2003

interior receiving a proximal end of the elongated ablation electrode.

3. (Cancelled).

4. (Currently Amended) An irrigation ablation probe according to claim 2, wherein the means for introducing fluid comprises an infusion tube attached to the proximal end of the elongated ablation electrode.

5. (Currently Amended) An irrigation ablation probe according to claim 2, wherein the elongated generally rigid probe body comprises a malleable material.

6. (Currently Amended) An irrigation ablation probe comprising:

[a] an elongated probe body having a length between proximal and distal ends and comprising an elongated tubular ablation electrode extending the length of the elongated probe body [~~at its distal end~~], the elongated tubular ablation electrode having at least one irrigation opening through which fluid can pass to the outside of the elongated tubular ablation electrode, the elongated probe body being generally rigid from its proximal end to its distal end so that the body cannot bend during ablation, and wherein the elongated tubular ablation electrode has an exposed distal portion is generally straight and forms an angle  $\alpha$  greater than  $0^\circ$  with the remainder of the elongated probe body;

Appln No. 09/370,601

Amdt date December 29, 2003

Reply to Office action of September 29, 2003

a non-conductive sheath positioned on the elongated tubular ablation electrode and configured to define the exposed distal portion;

a handle mounted to the proximal end of the elongated probe body, the handle comprising a housing having a generally open interior receiving a proximal end of the elongated ablation electrode; and

an infusion tube having proximal and distal ends and extending through the elongated probe body for introducing fluid into the elongated tubular ablation electrode, the distal end of the infusion tube being attached to the elongated tubular ablation electrode.

7. (Currently Amended) An irrigation ablation probe according to claim 6, ~~[wherein the generally rigid probe body comprises:~~

~~a tubular electrode having proximal and distal ends,~~] wherein the elongated tubular ablation electrode forms the infusion tube[~~;~~ and

~~a non-conductive sheath covering a portion of the tubular electrode].~~

8. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the elongated tubular ablation electrode is made of stainless steel.

9. (Currently Amended) An irrigation ablation probe according to claim [8] 6, wherein the elongated tubular ablation

Appln No. 09/370,601

Amdt date December 29, 2003

Reply to Office action of September 29, 2003

electrode has an inner diameter ranging from about 0.40 inch to about 0.80 inch and an outer diameter ranging from about 0.50 inch to about 0.90 inch.

10. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the elongated tubular ablation electrode has an outer diameter ranging from about 0.50 inch to about 0.70 inch.

11. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the elongated tubular ablation electrode has an inner diameter ranging from about 0.40 inch to about 0.60 inch.

12. (Cancelled).

13. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the elongated tubular ablation electrode is made of a malleable material.

14. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the proximal end of the elongated tubular ablation electrode is mounted in the handle.

15. (Currently Amended) An irrigation ablation probe according to claim [7] 6, further comprising a flexible plastic tubing attached to the proximal end of the elongated tubular

Appln No. 09/370,601

Amdt date December 29, 2003

Reply to Office action of September 29, 2003

ablation electrode for introducing fluid into the elongated tubular ablation electrode.

16. (Currently Amended) An irrigation ablation probe according to claim 15, wherein the flexible plastic tubing is attached to the proximal end of the elongated tubular ablation electrode within the handle.

17. (Cancelled).

18. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the at least one irrigation opening is located ~~[on]~~ in the exposed distal portion ~~[surface]~~ of the elongated tubular ablation electrode to be in contact with the tissue to be ablated.

19. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the elongated probe body has a length ranging from about 3.5 inches to about 12 inches.

20. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the elongated probe body has a length ranging from about 5 inches to 10 inches.

21. (Currently Amended) An irrigation ablation probe according to claim [7] 6, wherein the elongated probe body has a length ranging from about 7 inches to about 8 inches.

Appln No. 09/370,601

Amdt date December 29, 2003

Reply to Office action of September 29, 2003

22. (Currently Amended) An irrigation ablation probe according to claim [12] 6, wherein the exposed portion [~~region~~] of the elongated tubular ablation electrode has a length ranging from about 0.50 inch to about 1.5 inches.

23. (Currently Amended) An irrigation ablation probe according to claim [12] 6, wherein the exposed portion [~~region~~] of the elongated tubular ablation electrode has a length ranging from about 0.75 inch to about 1.25 inches.

24 to 39. (Withdrawn).

40. (Cancelled).

41 to 47. (Withdrawn).

48. (Currently Amended) An irrigation ablation probe according to claim 2, wherein the exposed distal portion of the elongated ablation electrode [~~has an exposed surface that~~] is conductive around a full circumference of the exposed distal portion [~~surface~~].

49. (Currently Amended) An irrigation ablation probe according to claim 6, wherein the exposed distal portion of the elongated tubular ablation electrode [~~has an exposed surface that~~] is conductive around a full circumference of the exposed portion [~~surface~~].

Appln No. 09/370,601

Amdt date December 29, 2003

Reply to Office action of September 29, 2003

50. (Cancelled).

51. (Currently Amended) An irrigation ablation probe according to claim 48, wherein substantially the entire exposed distal portion [~~surface~~] of the elongated ablation electrode is conductive.

52. (Currently Amended) An irrigation ablation probe according to claim 49, wherein substantially the entire exposed portion [~~surface~~] of the elongated tubular ablation electrode is conductive.

53. (Cancelled).

54. (Previously Presented) An irrigation ablation probe according to claim 2, wherein the angle  $\alpha$  ranges from greater than  $0^\circ$  to about  $270^\circ$ .

55. (Previously Presented) An irrigation ablation probe according to claim 2, wherein the angle  $\alpha$  ranges from about  $60^\circ$  to about  $140^\circ$ .

56. (Previously Presented) An irrigation ablation probe according to claim 2, wherein the angle  $\alpha$  is about  $90^\circ$ .

57. (Previously Presented) An irrigation ablation probe according to claim 6, wherein the angle  $\alpha$  ranges from greater than  $0^\circ$  to about  $270^\circ$ .

Appln No. 09/370,601

Amdt date December 29, 2003

Reply to Office action of September 29, 2003

58. (Previously Presented) An irrigation ablation probe according to claim 6, wherein the angle  $\alpha$  ranges from about  $60^\circ$  to about  $140^\circ$ .

59. (Previously Presented) An irrigation ablation probe according to claim 6, wherein the angle  $\alpha$  is about  $90^\circ$ .

60. (New) An irrigation ablation probe according to claim 2, wherein the at least one irrigation opening is located in the exposed distal portion of the elongated ablation electrode to be in contact with the tissue to be ablated.

61. (New) An irrigation ablation probe according to claim 2, wherein a plurality of irrigation openings are located in the exposed distal portion of the elongated ablation electrode to be in contact with the tissue to be ablated.

62. (New) An irrigation ablation probe according to claim 2, wherein the infusion tube and the elongated ablation electrode comprise a single generally hollow body.

63. (New) An irrigation ablation probe according to claim 6, wherein the infusion tube and the elongated tubular ablation electrode comprise a single generally hollow body.